

## DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Product Regulation)

**DoP \_ [EN] \_ 002 \_ No 52001135-1001**

1. Unique identification code of product-type:

**4TECX SILICONENKIT BASIC**

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):

Batch number: See product packaging

3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:

Sealants for façade elements  
Sealants for glazing  
Sealants for sanitary joints  
EN 15651-1: F-EXT-INT-CC (CLASS 12,5E)  
EN 15651-2: G-CC  
EN 15651-3: S (CLASS XS1)

4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):

**ZEVIJ-NECOMIJ □ TOUWSLAGERIJWEG 4 □ NL - 4906 RC OOSTERHOUT**

5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3  
System 3 for reaction to fire

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-2 / EN 15651-3 and reaction to fire under system 3 and issued a test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant

Essential characteristics	Performance	Harmonized technical specification
<u>Reaction to fire</u>	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
<u>Water tightness and air tightness</u>		
Resistance to flow	< 3 mm	
Loss of volume	< 25%	
Tensile properties at maintained extension after water Immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

Essential characteristics	Performance	Harmonized technical specification
<u>Reaction to fire</u>	Class E	EN 15651-2:2012
Release of chemical dangerous to the environment and health	NPD (*)	
<u>Water tightness and air tightness</u>		
<u>Loss of volume</u>	40 %	
<u>Vertical flow resistance</u>	< 3 mm	
Adhesion / cohesion properties after exposure to heat, water and artificial light	NF	
<u>Elastic recovery</u>	60 %	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	< 0,9 MPa	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 20 mm	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	≤ 0,9 MPa	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	1	
Durability	Pass	

(\*) See material safety data sheet

NPD: No Performance Determined

NF: No Failure

NR: Not required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by**



**Marc de Dobbelaere**  
Algemeen directeur